



AGILITY QUADRICEP P2.5

Flexible LED that curves walls, wraps columns, and becomes floors · 5-year warranty



ATTRIBUTES

- Makes complex and simple curves
- Flexible in multiple directions at once
- Durable
- Scalable
- Water & weather resistant to IP67
- Lightweight
- PowerCON / EtherCON connectors
- Daisy-chain power and data

SPECIFICATIONS

PIXEL PITCH	P2.5
RESOLUTION PER PANEL	120 × 120
BRIGHTNESS	4,500 NITS
DIMENSIONS	12" × 12" × 3.8" deep (304.8mm × 304.8mm)
MODULES PER PANEL	1
WEIGHT	4.78 lbs · reduced-weight option: 2.7 lbs
IP RATING	IP67 — indoor & outdoor
POWER CONSUMPTION	100W / 1A @ 110V AC per panel
BULBS & DRIVERS	Nationstar Gold · MBI or Chipone chips — flexible by build
LED TYPE	White SMD (Black available)
REFRESH RATE	3,840 Hz adjustable · up to 7,680 Hz with Brompton
GREYSCALE	14-bit standard · 16-bit available · 16 or 20 scan
TEMPERATURE RANGE	-14°F to 140°F
CABINET MOUNT	Magnetic — easy to install & service
PROCESSING	Novastar A8S (industry standard) · Brompton option
ASSEMBLED	USA — more than 50% at our New Jersey facility

BROMPTON PROCESSING OPTION — XR-ready with P3 color gamut HDR, refresh up to 7,680 Hz. Available on every pitch.



DESIGNED & ASSEMBLED IN NEW JERSEY, USA

Trusted by Disney, Disney Cruise Line, CBS Sports, and Entertainment Tonight.
Our panels sail aboard the Disney Wish.

AVAILABLE FOR PURCHASE OR FULL-SERVICE RENTAL